Course	chains	Section 30 Township 7 Range 5	variations
		About March 24th 1882 commenced survey in section 30 Township 7 North Range 5 West by request of ndsm Sinclair and Jonathan Baker. The principal object of this survey was to determine the proper location of the NW corner of said section 30 the field notes calling for a lap of 25 lks to determine if this was the true lap. I obtained the best legal advice I could and the principal enunciated by Judge John C. Robinson to govern the surveyor in his work was that the object should be to find when the corner was actually made by the gov. Surveyor and according to this the corner could not be located according to the laps in this case for evidence wherever found in this Town and Range as well as the surveys in general of John McDonald shows the laps left on record by him to be fictitious and not reliable. So the said NW corner of said section 30 was located and established 208 lks North of the corner of sections 24 & 25 T7R6 There was satisfactory evidence of the true location of the NE corner and the North half mile corner of the section and the line	

Course	chains		variations
		joining them was produced straight to the range line and the corner made at the intersection of these lines. Then I run	
South		From NE corner sec. 30	
	80.35	to SE	3° 53'
West		From SE sec 30 to SW	
North		From SW	
	38.17	E ¼ section 25-	
	80.22	NW cor sec 30	
East		From W¼ NW to E¼ NE	4°
		W¼ NW sec. 30 set stone marked (W¼ NW 30)	
		Post Oak 24 in N 27½ W 5 lk	
		Thomas Worden J. A. Brown } Chain carriers and Markers. David Klinger F.B.	
		Francis M. Parker. Co. Surveyor.	

Section 17, Township 7 Range 3

1882 Commenced survey in section 17 Township 7 North Range 3 West by request of John J. Combs and others hereafter named.

South		From NW corner sec. 17 set by P. Burr	
	39.58	to W¼ 31 lks W.	2° 56'
North		From E¼ SW sec 17	
	60.18	N¼ 8 lks W	2° 51'
West		From N¼ 17	
	39.61	NW corner 53 lks N	4° 15'
East		From W¼ 17	